Ordering information

Plastic enclosed safety switches



BWS325TPN



BWS425TPSN



BWS625TPN

Side operated safety switches, 3, 4 and 6-pole, IP65

Enclosure in robust thermoplastic (PBT). The safety switch comes complete with neutral, PE terminal, one N.O auxiliary contact, cable entries with metric threaded knock-outs, IP65 membrane glands. Cover interlock included.

Dark grey side-operated handle, dark grey cover

Cable entries from top and bottom

Max. motor output/ AC-23A			Enclosure dimensions					Weight /unit
415V	690V	Cable	Height	Width	Depth			
kW/A	kW/A	openings/side	mm	mm	mm	Type	Order number	kg
3-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xM25/2xM25	130	111	60	BWS316TPN	2CMA142417R1000	0.3
11/25	11/16	2xM32/2xM32+M16	168	138	68	BWS325TPN	2CMA142420R1000	0.4
Auxiliary contacts included: not included • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xM25/2xM25	130	111	60	BWS316FTPN	2CMA142440R1000	0.31
4-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xM25/2xM25	130	111	60	BWS416TPSN	2CMA142418R1000	0.32
11/25	11/16	2xM32/2xM32+M16	168	138	68	BWS425TPSN	2CMA142421R1000	0.42
6-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xø25.5+ø16.5/ 2xø25.5+ø16.5	130	190	130	BWS616TPN	2CMA142419R1000	0.54
11/25	11/16		130	190	130	BWS625TPN	2CMA142422R1000	0.54



BWS325YTPN



BWS425YTPN



BWS625YTPN

Red side-operated handle, yellow cover

Cable entries from top and bottom

Max. motor output/ AC-23A			Enclosure dimensions					Weight /unit
415V	690V	Cable	Height	Width	Depth			
kW/A	kW/A	openings/side	mm	mm	mm	Type	Order number	kg
3-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xM25/2xM25	130	111	60	BWS316YTPN	2CMA142423R1000	0.32
11/25	11/16	2xM32/2xM32+M16	168	138	68	BWS325YTPN	2CMA142426R1000	0.41
4-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xM25/2xM25	130	111	60	BWS416YTPSN	2CMA142424R1000	0.32
11/25	11/16	2xM32/2xM32+M16	168	138	68	BWS425YTPSN	2CMA142427R1000	0.42
6-pole. Threaded knock-out openings, also for control cables. Auxiliary contacts included: 1NO • Auxiliary contacts max: 1NO								
7,5/16	7,5/10	2xø25.5+ø16.5/ 2xø25.5+ø16.5	130	190	130	BWS616YTPN	2CMA142425R1000	0.54
11/25	11/16		130	190	130	BWS625YTPN	2CMA142428R1000	0.54

Compression glands or flanges to be ordered separately.